

COMPRESSORI D'ARIA CON TRASMISSIONE A CINGHIA



AIR COMPRESSORS

BELT DRIVEN AIR COMPRESSORS
COMPRESSEURS AVEC D'AIR TRANSMISSION À COURROIE
LUFTKOMPRESSOREN MIT RIEMENANTRIEB



GS12E/100/250/CAR/M



GS17E/200/330/CAR/T



1 Collettore di raffreddamento.



2 Doppia uscita.



3 Ruota pivotante.

24 ÷ 200 "E"

MODELLO Model	CODICE Code															
		Litri Liters	Litri/min Liters/min	CFM	min-1	Cilindri Cylinders	Stadi Stages	bar	psi	kW	HP	Volt	Hz	dB/A	L x P x H cm	Kg
GS12E/24/250/CAR/M	AF 004E	24	250	8,8	1.250	2	1	10	145	1,5	2	230	50	73	80x35x69	41
GS12E/50/250/CAR/M	AF 006E	50	250	8,8	1.250	2	1	10	145	1,5	2	230	50	72	90x35x72	45
GS12E/50/250/CAR/T	AF 007E	50	250	8,8	1.250	2	1	10	145	1,5	2	400	50	72	90x35x72	45
GS12E/100/250/CAR/M	AF 008E	100	250	8,8	1.250	2	1	10	145	1,5	2	230	50	72	115x37x80	62
GS12E/100/250/CAR/T	AF 009E	100	250	8,8	1.250	2	1	10	145	1,5	2	400	50	72	115x37x80	62
GS17E/100/320/CAR/M	AF 010E	100	320	11,3	1.500	2	1	10	145	2,2	3	230	50	74	115x37x80	65
GS17E/100/330/CAR/T	AF 011E	100	330	11,6	1.550	2	1	10	145	2,2	3	400	50	74	115x37x80	65
GS17E/150/320/CAR/M	AF 014E	150	320	11,3	1.500	2	1	10	145	2,2	3	230	50	74	135x45x98	78
GS17E/150/330/CAR/T	AF 015E	150	330	11,6	1.550	2	1	10	145	2,2	3	400	50	74	135x45x98	78
GS17E/200/320/CAR/M	AF 019E	200	320	11,3	1.500	2	1	10	145	2,2	3	230	50	74	150x50x103	88
GS17E/200/330/CAR/T	AF 020E	200	330	11,6	1.550	2	1	10	145	2,2	3	400	50	74	150x50x103	88

VOLTAGGI ED ESECUZIONI SPECIALI A RICHIESTA • VOLTAGES AND SPECIAL ASSEMBLIES ON REQUEST
TENSIONS ET FABRICATIONS SPÉCIALES SUR DEMANDE • SPANNUNGEN UND SONDERAUSFÜHRUNGEN AUF ANFRAGE